

PUBLIC ADDRESS / SPEAKERS / CEILING

GA-5027

LOW IMPEDANCE CEILING SPEAKER



- ✓ Excellent sound quality
- ✓ Excellent finish and elegant design
- ✓ Anchorage installation system

ESPECIALLY RECOMMENDED IN:



All sectors

DESCRIPTION

Coaxial ceiling loudspeaker for public address systemsIt delivers crisp, clean and rich sound, making it perfect for voice and musical ambience.It has a body made of ABS and a protective steel grille that guarantees its integrity.Its simple anchor installation system minimises assembly time, with the screws being completely hidden behind the grille.For background music and voice announcements in low-impedance installations in offices, shops, restaurants, waiting rooms, etc.

TECHNICAL CHARACTERISTICS

FEATURES	Low impedance coaxial ceiling loudspeaker with round grille.
POWER	40 W maximum, 25 RMS
LOUDSPEAKERS	5 ¼" coaxial
RESPONSE	60–20,000 Hz
IMPEDANCE	8 Ohm
SENSITIVITY	87 dB at 1 W/1 m
DISPERSION	130°
MATERIAL	ABS and steel grille
COLOUR	Greyish white (RAL 9003, RAL 7047)
DIMENSIONS	204 mm Ø x 70 mm depth
HOLE	165 mm Ø
WEIGHT	1 kg
	Quick installation system with catches