

PUBLIC ADDRESS / SPEAKERS / CEILING

GA-259

LOW IMPEDANCE CEILING SPEAKER



- ✓ Crisp and clean sound
- ✓ Compact size
- ✓ Quick installation system

ESPECIALLY RECOMMENDED IN:



All sectors

DESCRIPTION

Halogen spotlight size ceiling loudspeaker Its small size makes it unnoticeable in any installation. It delivers crisp,

clean sound, perfect for both speech and piped music. It stands out for its large coverage angle of 120°, which allows it to cover a larger area depending on the height of the ceiling. It has a quick installation system that minimizes assembly time.

TECHNICAL CHARACTERISTICS

FEATURES	Low impedance ceiling loudspeaker and round grille. Halogen bulb sized.
POWER	10 W maximum, 6 W RMS
LOUDSPEAKER	3"
RESPONSE	130-20,000 Hz
IMPEDANCE	8 Ohm
SENSITIVITY	87 dB at 1 W/1 m
DISPERSION	120° at 1 kHz 90° at 4 kHz
MATERIAL	Steel
COLOUR	White (RAL 9003)
DIMENSIONS	105 mm Ø x 50 mm depth
HOLE	85 mm Ø
WEIGHT	0.4 kg
	Quick installation system