

PUBLIC ADDRESS / SPEAKERS / EXPONENTIALS

## **FE-1110**

LOW IMPEDANCE HORN SPEAKER





Suitable for indoor and outdoor PA installations





Includes stainless steel mount

## ESPECIALLY RECOMMENDED IN:









Factories

Sports facilities

Education

All sectors

## **DESCRIPTION**

High impedance horn loudspeakerConstructed of ABS, aluminium and with stainless steel screws and bracket.



Water protection (IP-66) Suitable for indoor and outdoor PA installations. Excellent frequency response, perfect for public address applications. With an angle of coverage and sensitivity which allow the reach of great distances and coverage of large areas. Mount for easy installation, minimizing assembly time. For public address installations in large spaces, sports facilities, industrial buildings, shopping centres, schools, hospitals, etc.

## **TECHNICAL CHARACTERISTICS**

FEATURES	Low impedance horn speaker.
POWER	15 W RMS
RESPONSE	280-12,500 Hz
IMPEDANCE	8 Ohm
SENSITIVITY	105 dB at 1 W/1 m
DISPERSION	145° H x 95° V
PROTECTION	IP-66
MATERIAL	ABS Stainless steel screws and mount
COLOUR	Ivory (RAL 1015)
DIMENSIONS	22 x 16 x 23 cm depth
WEIGHT	1.1 kg