

PUBLIC ADDRESS / SPEAKERS / EXPONENTIALS

FE-1150T

100 V LINE TRANSFORMER HORN SPEAKER



IP66

- ✓ Suitable for indoor and outdoor PA installations
- ✓ It allows you to cover large areas and distances
- ✓ IP-66 protection
- ✓ Includes stainless steel mount

ESPECIALLY RECOMMENDED IN:



Factories



Sports facilities



Education



All sectors

DESCRIPTION

High impedance horn loudspeaker Constructed of ABS, aluminium and with stainless steel screws and bracket. Water protection (IP-66) Suitable for indoor and outdoor PA installations. Excellent frequency response, perfect for public address applications. With an angle of coverage and sensitivity which allow the reach of great distances and coverage of large areas. Various powers are available on the dial to choose the best volume for each application. Mount for easy installation, minimizing assembly time. For public address systems in 100 V line installations in large spaces, sports facilities, industrial buildings, shopping centres, schools, hospitals, etc.

TECHNICAL CHARACTERISTICS

FEATURES	Horn speaker with 100 V line transformer.
POWER	15 W RMS
RESPONSE	280-12,500 Hz
IMPEDANCE	15 W RMS@100 V (670 Ohm) 10 W RMS@100 V (1,000 Ohm) 5 W RMS@100 V (2,000 Ohm) 3 W RMS@100 V (3,300 Ohm) 1 W RMS@100 V (10,000 Ohm)
SENSITIVITY	105 dB at 1 W/1 m
DISPERSION	145° H x 95° V
SWITCHES	W selector in high Z
PROTECTION	IP-66
MATERIAL	ABS Stainless steel screws and mounts
COLOUR	Ivory
DIMENSIONS	22 x 16 x 23 cm depth
WEIGHT	1.3 kg