

PUBLIC ADDRESS / SPEAKERS / SURFACE



ACTIVE SURFACE SPEAKER PAIR





\oslash
\oslash
\oslash
\bigcirc

Great power and sound quality.

- Compact size
- High efficiency class-D amplifier
- Includes fixing bracket with swivelling arm and steel safety wire

ESPECIALLY RECOMMENDED IN:



Hospitality

Retail







All sectors



DESCRIPTION

Pair of low impedance loudspeakers from the AMBIENT series. Specially designed for public address and ambient sound applications; a solution for installations in public premises such as restaurants, cafeterias, supermarkets, shopping centres, etc.Excellent finish, high power and resistant, in a reduced size.The loudspeakers include a wall mount with swivel arm and steel safety cable, allowing for easy installation and orientation of the loudspeakers.They are a great solution for installations in public places such as restaurants, cafés, supermarkets, shopping centres, etc.

TECHNICAL CHARACTERISTICS

FEATURES	Pair of autoamplified compact Hi-Fi loudspeakers. Both active loudspeakers with amplifier. Highly efficient class-D amplifier. Loudspeaker with shielded magnet. Bass reflex reinforcement system.
POWER	40 W maximum, 20 W RMSClass-D amplifierProtection compressor/limiter
LOUDSPEAKERS	1 x 3" polypropylene woofer, 20.4 mm coil with shielded magnet
RESPONSE	132-20,000 Hz
INPUTS	1 aux line, 2 x RCA 775 mV 1 balanced line, 6.3 mm jack 775 mV
OUTPUTS	1 balanced line, 6.3 mm jack
INDICATOR	Power
CONTROLS	On/off and volume
COLOUR	White (RAL 9010)
POWER SUPPLY	230 V AC, 40 W 115 v AC on request
DIMENSIONS	115 x 175 x 107 mm depth
WEIGHT	2 x 1.3 kg
ACCESSORIES	Wall mount with adjustable arm and steel safety cable