

PUBLIC ADDRESS / SPEAKERS / SURFACE



100 V LINE TRANSFORMER, LOW IMPEDANCE SURFACE SPEAKER PAIR







OOO

Excellent sound quality Excellent finish and elegant design IP-56 protection

Adjustable fixing mounts included



ESPECIALLY RECOMMENDED IN:





DESCRIPTION

Pair of surface-mount loudspeakers with 100 V line transformer and low impedance. The ELIPSE range is specially designed for PA and surround sound applications. The speakers feature excellent finish, elegant design, high power capacity and durability. They include a wall mount that can be swivelled in all directions for easy installation. Prepared for outdoor use, water protection and anti-corrosion materials. They are a great solution for installations in public places such as restaurants, cafés, supermarkets, shopping centres, etc.

TECHNICAL CHARACTERISTICS

FEATURES	Pair of low impedance loudspeakers with 100 V line transformer. Designed for outdoor use, water-resistant and rustproof materials.
POWER	120 W maximum, 60 W RMS
LOUDSPEAKERS	1 x 8" polypropylene woofer 1 x 1" silk dome tweeter
RESPONSE	30-20,000 Hz
IMPEDANCE	High Z 100 V line: 200 Ohm (50 W) 400 Ohm (25 W) 800 Ohm (12.5 W) 1,600 Ohm (6.25 W) Low Z: 8 Ohm
SENSITIVITY	90 dB at 1 W/1 m
SWITCH	W selector in high Z and low Z
PROTECTION	IP-56
MATERIALS	Aluminium grille Weatherproof mount Stainless steel screws
CONNECTORS	Spring terminals
COLOUR	Black (RAL 9017)
DIMENSIONS	244 x 378 x 240 mm depth
WEIGHT	2 x 5 kg
ACCESSORIES	Adjustable fixing mounts