

PUBLIC ADDRESS / SPEAKERS / SOUND COLUMNS

FCS-21

100 V LINE TRANSFORMER AND LOW IMPEDANCE COLUMN SPEAKER



- ✓ Excellent sound quality
- ✓ Absence of feedback and reverberation
- ✓ Directional sound to the audience area

ESPECIALLY RECOMMENDED IN:



All sectors

DESCRIPTION

Compact sized, stylish column speaker with reduced visual impact. Excellent acoustic features, high quality audio and steering which allows the sound to be directed at the listening area. Manufactured in aluminium with 2" moisture resistant loudspeakers.

TECHNICAL CHARACTERISTICS

FEATURES	Column speaker with 100 V line transformer and low impedance. High quality audio and reduced visual impact.
POWER	20 W
LOUDSPEAKERS	12 of 2"
RESPONSE	152-20,000Hz
IMPEDANCE	High Z 100 V line: 500 Ohm (20 W) 670 Ohm (15 W) 1,000 Ohm (10 W) 2,000 Ohm (5 W) Low Z: 8 Ohm
SENSITIVITY	89 dB at 1W/1m
DISPERSION	140° h x 30° v
SWITCHES	W selector in high Z, low Z and 'off'
CONNECTORS	Screw terminals
MATERIAL	Grey anodized aluminium
DIMENSIONS	7 x 83.6 x 9 cm depth
WEIGHT	3.5 kg
ACCESSORIES	Adjustable fixing mounts