

HIGH POWER / AUXILIARY EQUIPMENT / AUDIO DISTRIBUTORS

FDT-112

AUDIO SPLITTER



- ✓ Converts 1 input to 5 stereo outputs
- ✓ Independent volume controls per output
- ✓ Operating mode selector: mono/stereo
- ✓ Input level indicator lights.
- ✓ Ideal for sound systems, press splitters etc.

ESPECIALLY RECOMMENDED IN:



All sectors

DESCRIPTION

Audio Splitter Allows 1 line signal to be converted into 10 mono outputs or 5 stereo outputs. Distributes the audio signal to sound systems, press distributors, among others. Volume per output. Operating mode selector: mono or stereo. GND lift ground disconnect Among its most outstanding uses are press rooms, conference rooms, among others.

TECHNICAL CHARACTERISTICS

FEATURES	Audio splitter with 1 mono input to 10 mono outputs or 1 stereo input to 5 stereo outputs. LED input level indicators.
INPUTS	2 balanced lines, combo (XLR and 6.3 mm stereo jack) 15,000 Ohm 775 mV
OUTPUTS	10 balanced lines, XLR 600 Ohm 775 mV 2 balanced link output lines, XLR 600 Ohm 775 mV
CONTROLS	Output volume Function mode selector: mono, stereo GND lift earth disconnection
RESPONSE	20-20,000 Hz
DISTORTION	Harmonic: < 0.05%
S/N RATIO	> 90 dB
POWER SUPPLY	230/115 V AC, 10 W maximum
DIMENSIONS	483 x 44.5 x 215 mm depth. 1 U 19" rack
WEIGHT	2.6 kg