

MICROPHONES / CONFERENCE SYSTEMS / DIGITAL

SCD-610P

CHAIRMAN MICROPHONE FOR DIGITAL CONFERENCE SYSTEM



- ✓ Crystal clear voice pick-up
- ✓ Priority and control over delegate microphones.
- ✓ Information display
- ✓ Voting buttons.
- ✓ Monitor speaker and gooseneck microphone

ESPECIALLY RECOMMENDED IN:



Education



Offices

DESCRIPTION

President microphone President microphone for conference system mod. SCD-600. Priority and control over delegate microphones, LCD information display, voting buttons, monitor loudspeaker and headphone output, in addition, they do not require any additional power supply and are immediately recognised by the SCD-600 central unit without configuration. Cat 5e, Cat 6 cable connection. Conference rooms, plenary sessions, parliaments, business centres, etc.

TECHNICAL CHARACTERISTICS

| | |
|-------------|---|
| FEATURES | <p>President microphone. Priority and control over delegated microphones. Information display. Voting buttons. Built-in monitor speaker. Gooseneck microphone. Data and audio transmission. Cat 5e, Cat 6 cable connection (see note).</p> |
| MICROPHONE | <p>Unidirectional electret condenser with luminous ring</p> |
| DIMENSIONS | <p>Gooseneck microphone: 440 mm Base: 170 x 39 x 172 mm depth</p> |
| WEIGHT | <p>0.7 kg</p> |
| ACCESSORIES | <p>Windshielded foam Cat 5e / FTP network cable with shielded connectors, 2 m length</p> |
| NOTE | <p>It is necessary to use high quality Cat 5e/6 cables with FTP/SFTP shielding, 24 AWG. Cables should have shielded connectors with the cable shielding connected to the connector shield. Maximum cable length 100 m. Cables between microphones should not exceed 2-3 metres.</p> |