

DATA SHEET

MICROPHONES / SURFACE MICROPHONE / CONDENSER



BOUNDARY CONDENSER SURFACE MICROPHONE



OOOO

Crystal clear voice pick-up Selectable directivity pattern Touch switch with power-on indicator light Filter: Bass cut/flat response PTT/PTL function



ESPECIALLY RECOMMENDED IN:





Centers of Worship

Education

Offices

DESCRIPTION

Electret condenser boundary microphone with tactile switch and LED power indicator.Selectable directivity pattern and power mode.Stylish design and robust construction. Non-slip rubber base. High quality sound.

TECHNICAL CHARACTERISTICS

FEATURES	Ultra slim boundary microphone for use on tables, walls, etc. Sharp pick-up. Tactile power switch with LED power indicator.
CAPSULE	Electret condenser Selectable directivity pattern: omnidirectional, sub-cardioid, cardioid, super-cardioid and bidirectional
RESPONSE	50-15,000 Hz
SENSITIVITY	-32 dB ±3 dB (V/Pa)
IMPEDANCE	200 Ohm
SWITCH	Mic.: tactile on/off Filter: bass cut-off/flat response Initial status: power on/off Operating: PTT/PTL
INDICATOR	LED power indicator
CONNECTORS	Mini male XLR output
PHANTOM	48 V DC
CABLE	3 m with mini female XLR and male XLR connectors Balanced line
DIMENSIONS	92.5 x 26 x 100 mm depth
COLOUR	Black
WEIGHT	0.15 kg