

MICROPHONES / TRANSLATION SYSTEM / SIMULTANEOUS

SCT-600

SIMULTANEOUS INTERPRETATION TRANSMITTER



ESPECIALLY RECOMMENDED IN:



Education



Offices

DESCRIPTION

Simultaneous interpretation system for up to 5 languages with transmission via IR radiators. Allows connection of up to 6 translation desks. High sound quality without interference with lighting systems.

TECHNICAL CHARACTERISTICS

FEATURES	<p>Transmitter of the SCT simultaneous translation system.</p> <p>Up to 5 languages, in addition to the original language.</p> <p>Connection of up to 10 SCT-61M or SCT-122M microphones in cascade.</p> <p>Auto output volume control.</p> <p>Transmission of the base channel (Channel 0) on the channel that the translator microphone is switched off.</p> <p>Built in compliance with IEC 60914 Conference Systems and IEC 61603-7 Transmission Systems standards.</p>
RESPONSE	100-14,000 Hz
INDICATORS	Output level in each channel
INPUTS	6 lines, RCA 18,000 Ohm 2 V
OUTPUTS	<p>6 lines, RCA 600 Ohm 1 V</p> <p>2 radiators, BNC 50 Ohm</p> <p>2 interpretation units, DB25</p>
S/N RATIO	>75 dB
POWER SUPPLY	110-240 V AC, 40 W
DIMENSIONS	483 x 89 x 390 mm depth
WEIGHT	7 kg
ACCESSORIES	<p>10 m interconnection cable for interpretation units, DB25</p> <p>2 x audio cables, 6.3 mm mono jack to RCA</p>