

RACKS AND TRANSPORT FURNITURE / 19" RACKS / FLOOR CUPBOARDS

## FRA-42600S-SKD

DISASSEMBLED 19" 42 U METAL RACK CABINET



(S)

Centralises and protects equipment from unwanted tampering, knocks, etc.



Very strong construction



Transparent tempered glass door with lock and key



Features wheels with brakes, feet, thermostat and 4 ceiling fans



Removable side and back panels, with lock and key



ESPECIALLY RECOMMENDED IN:



All sectors

## **DESCRIPTION**

19" rack cabinet19" metallic rack cabinet 19" 42 U for floor mounting. It allows you to keep all equipment in your facility safe and secure in one place. It has a transparent tempered glass front door with lock, key and possibility to change the opening direction, wheels with brake, feet, removable side and rear panels with lock and key, thermostat and 4 ceiling fans (230 V AC). It is an ideal solution for installing telecommunications equipment, networks, servers, etc. The depth of the rack makes it possible to mount equipment up to 60 cm deep. This rack cabinet protects the equipment and allows access to them, both through the front door and through its side and rear panels, which greatly facilitates access to the equipment for maintenance and monitoring. Possibility of lateral union with cabinets model: FRA-47800W, FRA-42800W and FRA-42600S. It is delivered disassembled with instructions and mounting accessories. Includes screws and nuts for installation of equipment. For sound, lighting, data, communications, etc.

## **TECHNICAL CHARACTERISTICS**

FEATURES	19" metallic rack cabinet.  Transparent tempered glass front door with lock, key and possibility to change the opening direction.  Removable side and rear panels, with lock and key.  Thermostat and 4 ceiling fans (230 VAC).  Wheels with brake and feet.  Possibility of lateral union with cabinets model: FRA-47800W, FRA-42800W and FRA-42600S.  Black enamel finish.  It is delivered disassembled with instructions and mounting accessories.
CAPACITY	42 U of 19" rack = 187 cm
DIMENSIONS	With wheels: 600 x 2070 x 800 mm depth Thickness of metal sheets: 1.2 mm Thickness of guide rails: 2 mm
COLOUR	Black (RAL 9011)
WEIGHT	96 Kg
ACCESSORIES	Screws and nuts for device installation