

SYSTEMS AND CONTROL / MESSAGE PROGRAMMING / DIGITAL

ZSM-1050

MULTI-ZONE MESSAGE SCHEDULER, BACKGROUND MUSIC PLAYER AND SIP CLIENT



- ✔ Allows playback of scheduled and instant messages
- ✔ SIP client for connection to PBX and SIP devices
- ✔ Triggering of alarms and events by contact closure
- ✔ Easy programming with PC software

ESPECIALLY RECOMMENDED IN:



Factories



Education



Hotels



All sectors

DESCRIPTION

Message programmer, events and background music player with 4 output zones. Internal clock function with automatic daylight saving time update. Programmed, live message player and alarms. And plays background music from internal memory or USB/SD, creation of multiple background music channels. Alarm activation through contact closure. Easy programming with PC software, management via local area network (LAN) and internet.

TECHNICAL CHARACTERISTICS

FEATURES	<p>Message scheduler, event scheduler, background music player and SIP client with 4 outgoing zones.</p> <p>Internal clock function with automatic daylight saving time update.</p> <p>Temporary scheduling of general purpose messages and outputs. Play live messages.</p> <p>Triggering of alarms and events by contact closure.</p> <p>Dedicated player for messages, alarms (internal memory) and VoIP. It does not interrupt background music.</p> <p>Ambient music player from USB/SD or internal memory with multi-channel creation.</p> <p>SIP protocol.</p> <p>PC software for programming, management and transfer of audio files via local area network (LAN) and internet.</p> <p>Priority of alarms and messages on background music inputs.</p> <p>16 GB internal memory for audio files.</p> <p>USB port and SD card reader for audio file playback and software update.</p>
INPUTS	<p>1 background music aux, 2 x RCA 1 V</p> <p>4 programmable inputs for alarm activation through contact closure, euroblock</p> <p>1 ethernet, RJ-45</p>
OUTPUTS	<p>4 zones, 2 x RCA 2 V</p> <p>4 general purpose relays, euroblock</p> <p>2 link for future applications, RJ-45</p>
POWER SUPPLY	<p>100-240 V AC, 9 W and 24 V DC, 0.4 A</p>
DIMENSIONS	<p>435 x 45 x 220 mm depth. 1 U 19" rack</p>
WEIGHT	<p>2.7 kg</p>
ACCESSORIES	<p>Mounts for assembly in 19" rack</p>

SOFTWARE

PC software ZSM-GO (included)
Access via local area network (LAN) and internet
Multiple ZSM control and management
Message programming and general purpose outputs
Alarm and alarm input configuration
Creation and control of background music channels
Audio file transfer and management
Status monitoring

