

SYSTEMS AND CONTROL / ZONE SYSTEMS / DIGITAL

MPX-460P

REMOTE CONTROL FOR VOLUME CONTROL AND ZONE AND SCENE ASSIGNMENT WITH TOUCH SCREEN









Enables volume control, zone assignment, scene assignment, etc.

ESPECIALLY RECOMMENDED IN:



DESCRIPTION

The MPX-4088 system is a highly versatile audio matrix, perfect for installations of any size, allowing a multitude of configuration options, DSP signal processing and integrated solutions to common problems such as feedback, covering almost any installation need. MPX-460P is a remote volume control and zone assignment remote



control with touch screen for audio matrix mod. MPX-4088.It connects to the matrix via RJ-45, Cat 5e cable and has an extension link to connect up to 8 MPX-460P in series.For installations where there are various audio sources and audience areas such as shopping malls, hotels, conference rooms, stadiums, etc.

TECHNICAL CHARACTERISTICS

| FEATURES | Remote control for volume control and zone assignment with touch screen for audio matrix mod. MPX-4088. Connection to the matrix via RJ-45 cable, Cat 5e (see note). Link extension for connecting up to 8 MPX-460P in series. Capacitive LCD touch screen. Surface installation. The rear panel is screwed to the wall and the front panel is secured with a screw. |
|--------------|--|
| INPUTS | 1 RD port for connection to MPX-4088 matrix, RJ-45 (see note) |
| OUTPUTS | 1 extension link, RJ-45 |
| CONTROLS | Volume control, zone and scene allocation |
| POWER SUPPLY | 24 V DC, 100 mA, RD port 24 V DC, 300 mA, euroblock, for connection of more MPX-460P in series. |
| DIMENSIONS | 150 x 115 x 25 mm depth Surface installation. |
| WEIGHT | 0.29 kg |
| ACCESSORIES | Screws and mounting accessories |
| NOTE | It is recommended to use high quality Cat 5e/6 cables, UTP or FTP/SFTP shielded cables with shielded connectors and with the cable shield connected to the connector shield. Maximum cable length 100 m. |

